

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number  
**WO 2004/009944 A1**

(51) International Patent Classification<sup>7</sup>: E06B 3/663

(21) International Application Number:  
PCT/CA2003/001091

(22) International Filing Date: 18 July 2003 (18.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/396,722 19 July 2002 (19.07.2002) US

(71) Applicant and

(72) Inventor: LAFOND, Luc, Marcel [CA/CA]; 23 Wood-  
valley Drive, Etobicoke, Ontario M9A 4H9 (CA).

(74) Agent: BUTSKY, Victor, V.; Deeth Williams Wall LLP,  
150 York Street, Suite 400, Toronto, Ontario M5H 3S5  
(CA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: FLEXIBLE CORNER FORMING SPACER



(57) **Abstract:** A tubular spacer core (50) may be used to manufacture an insulated glass assembly. The core is hollow and has a plurality of bending zones along its length. Each bending zone includes a plurality of circumferential ribs (53). Each rib has sides (57, 59) of unequal length. The ribs re-enter and overlap their adjacent ribs when the core is bent along the longitudinal axis of the core. The ribs (53) lock in place to form a sharp corner at the inner edge (52), at the bend. The ribs (53) unfold and expand at the outer edge (54), at the location of the bend. The core (50) may also include a layer of desiccant and a vapor barrier. Adhesive is used to secure the appropriately shaped core between a pair of opposing glass plates, to manufacture an insulated glass assembly.